



Technical data **MobiSCREEN**

Display size	18.5"	21.5"
Resolution	1366 x 768 (WXGA)	1920 x 1080 (Full HD)
Contrast	1,000:1	5,000:1
Viewing angle	170°/160°	178°/178°
Weight	approx. 7 kg	approx. 8 kg
Power consumption	max. 21 W	max. 26 W
Format	16:9	
Brightness	min. 300 cd/m ²	
Colours	16.7 million, 24 Bit	
Housing	anodised aluminium	
Operating voltage	24 VDC (16.8 - 32 VDC)	
Operating temperature	0 °C to +50 °C (Security switch-off outside this range)	
Interfaces	IP/Ethernet, USB optional: RS485, IBIS	
Editing software	MCE (Mobitec Content Editor) and MAW (Mobitec Access Web)	
Data and firmware update	manually from USB flash memory automatically via IP/Ethernet Interface with MAW (Mobitec Access Web)	
Operating system	Linux	
Standards and directives	ECE-R10, Rev.04 (EMC-Bus)	

Compact TFT screen with elegant aluminium profile.

Vandal-proof design with toughened safety glass.

Can display different kinds of information:

- Next stop
- Detailed route information with connections
- Network map
- Newsticker
- Advertisement (text, video and image) as additional source of income

Customised layout in your corporate design possible.

LED backlight.

Low weight.

Flexible mounting concept.

Low maintenance: no moving parts, fanless heat management.