



Technical data **MobiSTOP**

LED colour	amber or green
Resolutions	height: up to 16 lines width: up to 144 columns (Exact resolutions available on request)
Operating voltage	24 VDC (17 - 32 VDC)
Power consumption	< 1.5 A (depending on sign size)
Operating temperature	-25 °C to +70 °C
Interfaces	direct: RS485 or IBIS via control unit: IBIS, Ethernet, RS232
Editing software	MIE (MobilInfoEdit)
Data and firmware update	manually via control unit from USB flash memory automatically via IP/Ethernet Interface (wireless and FTP service optionally available)
Standards and directives	VDV300 (IBIS) EMC ECE-R10, Rev. 04 (EMC-Bus) Type approval number: (E5) 10R-04179

Next stop sign with either permanent text for “bus stopping” or alternating “bus stopping” signal.

Back-to-back installation possible.

Optimum readability at all times thanks to automatic brightness control.

Robust and durable design with protective glass cover.

Maintenance-free.

SCANNOTEC OY
Tillinmäentie 3 B · 02330 Espoo
Puh. 020 7288 530
info@scannotec.fi · www.scannotec.fi



Mobitec AB

Ölltorps Industriområde 4, Box 97 · 524 21 Herrjunga · SWEDEN · Phone: +46 513 229 00 · Fax: +46 513 107 22
info@mobitec.eu · www.mobitec.eu

AUSTRALIA · BRAZIL · GERMANY · INDIA · SWEDEN

